

『耳川の杉』製品規格表

区分	名称	長 [m]	厚 [mm]	幅 [mm]	備考	区分	名称	長 [m]	厚 [mm]	幅 [mm]	備考				
角 類	柱	3	105	105	KD・AD・GR	板 類	貫	4	13	90	AD・GR				
			120	120					13	105					
	母屋	4	90	90	KD・AD・GR				ラス下 地板	3		12	90		
			90	90								12	105		
			105	105								15	90		
			120	120			15	105							
			梁・ 桁	3			105	150	KD・AD・GR	板	4	24	150		
	105	180			24		180								
	105	210			30		150								
	105	240			30		180								
	間柱	3			27		105	KD・AD・GR		足場 板	4	35	200	波 釘	
					27		120					36	240		
筋 かい					4	30	105			KD・AD・GR	小巾 板	2	12	60	
						30	120						12	90	
	45	105	12	105											
	垂木	3	40	40		AD・PG	加工 板	4	12		120	KD壁板			
			45	45					12		100				
			45	54					15		100	KD床板			
45			60	30	100										
集成材	双子柱	3	105	105	AQ認証	筋 かい	3	45	105	FJ・中空					
			120	120				45	120						
	間柱	3	30	105	FJ			40	150						
			30	120											
筋 かい	3	45	105	FJ・中空	40	150									
		45	120												

※ KD=人工乾燥材、AD=天然乾燥材、GR=グリーン材、PG=プレーナギャング
FJ=フィンガージョイント、中空=中空間柱